Mobil Delvac XHP 10W-40

[illegible]

[illegible]

Mobil Delvac XHP 10W-40 - [illegible]

[illegible]

[illegible] Mobil Delvac XHP 10W-40 [illegible] Mobil Delvac XHP 10W-40.

[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible] ("[illegible]-[illegible]-[illegible]")
[illegible]	[illegible]
[illegible]/[illegible]	[illegible]
[illegible]	[illegible]

[illegible] ExxonMobil
[illegible]: www.exxonmobil.com.
[illegible] ExxonMobil [illegible] Esso, Mobil [illegible] ExxonMobil. [illegible]
[illegible] ExxonMobil. [illegible] © 2001 Exxon Mobil Corporation. [illegible]

[illegible]

- [illegible]
- [illegible]
- [illegible]

[illegible]

Mobil Delvac XHP 10W-40 [illegible]:
ACEA E3/B4/B2

Mobil Delvac XHP 10W-40 [illegible]:
Daimler Chrysler MB 228.3
MAN M3275
Volvo VDS-2
Scania LDF
Renault RVI RD

Mobil Delvac XHP 10W-40 [illegible]:
API CF

Typical Properties

Mobil Delvac XHP 10W-40	
SAE [illegible]	10W-40
[illegible], ASTM D 445	
[illegible] 40°C	85
[illegible] 100°C	13.6
[illegible], ASTM D 2270	163
[illegible], %[illegible], ASTM D 874	1.7
[illegible] KOH/[illegible], ASTM D 2896	16.4
[illegible], °C, ASTM D 97	-33
[illegible], °C, ASTM D 92	220
[illegible] 15°C [illegible], ASTM D 4052	0.872

[illegible] ExxonMobil [illegible]: www.exxonmobil.com. [illegible] ExxonMobil [illegible] Esso, Mobil [illegible] ExxonMobil. [illegible] ExxonMobil. [illegible] © 2001 Exxon Mobil Corporation. [illegible]

[illegible]

[illegible]

[illegible] Mobil, [illegible] Delvac [illegible] ExxonMobil Corporation, [illegible]e [illegible].

[illegible] ExxonMobil
[illegible]: www.exxonmobil.com.
[illegible] ExxonMobil [illegible] Esso, Mobil [illegible] ExxonMobil. [illegible]
[illegible] ExxonMobil. [illegible] © 2001 Exxon Mobil Corporation. [illegible].